

VERSA-LOC PRODUCT SPECIFICATIONS AND INSTALLATION

PART 1 – PHYSICAL CHARACTERISTICS

1. Versatile and able to withstand heavy loads.
2. Slip resistant, sound absorbent and easy to install and move.
3. Easily maintained by wiping with a damp cloth or light vacuuming.
4. Excellent drainage capability.

PART 2 – PHYSICAL SPECIFICATIONS

- | | |
|--|---|
| 1. Material: | Environmentally friendly, UV-stabilized polypropylene |
| 2. Style: | Interlocking tile, optional beveled edges and corners available |
| 3. Thickness: | 3/8" |
| 4. Weight: | 0.60 lbs/sq ft or 0.91 lbs/tile |
| 5. Standard Sizes: | Tiles: approximately 1.24' x 1.24' (37.8 cm x 37.8 cm)
Beveled Edges: 2.16" x 1.24'; Corner: 2.16" x 2.16" |
| 6. Standard Tile & Edging Colors: | Gray, Blue, Sand, Graphite |
| 7. Case Pack | 35 tiles per case, 53.8 sq ft – full cases only |
| 8. Brittleness Temperature (ASTM D746) | <= 73°F |
| 9. Tensile Strength (ASTM D638) | 3,770.98 psi or 26 Mpa |
| 10. Density (ASTM D1505) | 902 kg/m ³ |

PART 3 – INSTALLATION

1. Start installation in a corner and install the tiles in an angle.
2. Fix the connection tabs over the protruding rings.
3. Distinctly tapping a rubber mallet over the connections tabs interlocks the tiles together.
4. Use a jigsaw to cut the tiles for a perfect fit.
5. Attach edge and corner strips for a smart and safe finish of your floor.

PART 4 – APPLICATIONS

1. Balconies
2. Terraces
3. Pool Areas
4. Patios
5. Garages
6. Storage Areas
7. Laundry Rooms
8. Entrance Halls

PART 5 – WARRANTY

Limited 5-Year Warranty: Allied Products, LLC guarantees its Versa-Loc outdoor tiles against deterioration due to faulty materials or workmanship. This guarantee does not cover damage that could occur from other abuses beyond the general intended application of the product. No other warranty is expressed or implied. Limit of liability from any losses resulting from the use of this product shall be for the purchase price only, and applied in the form of credit, excluding any freight charges.